

FD
918

CENTRAL INTELLIGENCE AGENCY

INFORMATION REPORT

This Document contains information affecting the National Defense of the United States, within the meaning of Title 18, Sections 793 and 794, of the U.S. Code, as amended. Its transmission or revelation of its contents to or receipt by an unauthorized person is prohibited by law. The reproduction of this form is prohibited.

SECRET/CONTROL - U.S. OFFICIALS ONLY
SECURITY INFORMATION

25X1

COUNTRY	East Germany	REPORT	
SUBJECT	Wismut A.G.: New Pithead Installations	DATE DISTR.	22 September 1953
DATE OF INFO.		NO. OF PAGES	2
PLACE ACQUIRED		REQUIREMENT NO.	RD
		REFERENCES	

25X1

THE SOURCE EVALUATIONS IN THIS REPORT ARE DEFINITIVE.
THE APPRAISAL OF CONTENT IS TENTATIVE.
(FOR KEY SEE REVERSE)

25X1

Wismut A.G. (Third Administration) approved the installation of the following new plant:

a. Object 90, pit 356:

- 5 car tippers (sideways), of which three rotate to the right and two to the left (Kreiselwipper),
- 3 mechanical spreaders (Schubwagenspeiser).
- 1 traveling platform (Schiebebuehne),
- 3 foot stoppers (Fusstopper).
- 1 electromagnetic stopper.
- 3 electromagnetic switch mechanisms (Weichenantriebe)
- 4 conveyorbelts, 22.5, 22.5, 10.4, and 24 m. x 650 mm.
- 5 pneumatic double swinging sliding closings 900/900 mm. (Doppelschwingschieberverschluesse).
- 6 switches (five right, one left) (Weichen).
- 6 chutes (Schurren).
- 1 right junction section (Uebergangs-Stueck)

Five bunkers of 20 cu. m. capacity are already available locally.

b. Object 90, capstan installation for opencast pit "Kerfer 3". (Spillanlage)

- 1 winch Tl. 3, 3,000 kg., with 18 kw motor. (Haspel)
- 240 m. winding cable, 15 mm. diameter (Zugseil).
- 4 capstan drums (Spill-Koepfe).

25X1

SECRET/CONTROL - U.S. OFFICIALS ONLY

25 YEAR RE-REVIEW

STATE	X	ARMY	X	NAVY	X	AIR	X	FBI		AEC	X						
-------	---	------	---	------	---	-----	---	-----	--	-----	---	--	--	--	--	--	--

(Note: Washington Distribution Indicated By "X"; Field Distribution By "#")

SECRET/CONTROL - U.S. OFFICIALS ONLY

25X1

- 2 -

The shunting pull (7) (Rangiersuz) is 200 m., horizontal; the "Abhaengepunkt" of Track 1 is 21 m. from the machine, of Track 2 is 25 m.

c. Object 90, Sorge Nord, track drainage project.

25X1

1,230 m concrete drainpipe (of which 990 m. of 150 mm. the remainder of 200, 250 and 350 mm. diameter).

33 m. steel pipe, 350 mm. diameter.

32 brick shafts 0.6 m. square, with concrete covers.

9 brick shafts 0.8 m. square, with concrete covers.

80 m stone drain 0.8 m. broad, 0.3 m. deep.

SECRET/CONTROL - U.S. OFFICIALS ONLY